

Model No.	Nominal Capacity		Nominal Voltage	Dimensions (mm)			Weight approx
	Typical	Min		Height	Width	Thickness	
	(mAh)	(mAh)	V	(±1)	(±0.5)	(±0.3)	g
302024FE	55	50	3.2	23	19.5	2.8	1.5
451230FE	60	55	3.2	30	12	4.3	2
652438FE	330	310	3.2	38	23.5	6.2	9
554050FE	650	600	3.2	50.5	39.5	5.2	18
784951FEHR	1100	1000	3.2	51	48.5	7.5	31
784951FER	1150	1050	3.2	51	48.5	7.5	45
564755FE	1800	1700	3.2	55	46.5	5.3	35
854755FE	1380	1300	3.2	55	46.5	8.2	35
383466FE	560	520	3.2	66	33.5	3.6	15
752567FER	750	700	3.2	67	24.5	7.2	24
402876FE3R	435	410	3.2	76	27.5	3.8	12.4
856877FE	2900	2750	3.2	77	67.5	8.2	85
856877FEM	3000	2800	3.2	77	67.5	8.2	85
804080FE	2200	2100	3.2	80	40	8	49
705880FE	2250	2100	3.2	80	57.5	6.7	51
805590FERE	2300	2200	3.2	90	54.5	7.7	74
883496FEHRN	1800	1700	3.2	95	34	8.8	54
8634125FE	2500	2400	3.2	125	33.5	8.3	65
11065130FERSE	6500	6000	3.2	130	64.5	10.7	216
8445135FEHR	3000	2800	3.2	135	44.5	8.1	96
8360145FE	5200	4900	3.2	145	59.5	8	134
90133200FERSE	20000		3.2	200	133	9	482
10867220FERE	10000	9500	3.2	219	67	11	300
8090220FERSE	10000	9500	3.2	219	89.5	7.7	296
9567220FEHR2E	6500	6000	3.2	220	66	9.4	235
5067220FERSE	4000	3800	3.2	220	66.5	4.8	135
5367220FER2E	4000	3800	3.2	220	66.5	5	135
13067220FER2E	10000	9500	3.2	220	67	13.5	330
9084220FERSE	9700	9200	3.2	220	83.5	8.7	305
7590222FER2E	7500	7000	3.2	220	90	7.2	230
10090222FER2E	10000	9500	3.2	220	90	9.7	338
5090222FE4RSE	4000	3800	3.2	222	89.5	4.8	170
6090222FE4RSE	4000	3800	3.2	222	89.5	5.7	210
7590222FE4RSE	4000	3800	3.2	222	89.5	7.2	216
7590222FEHR2E	7500	7000	3.2	222	90.5	7.2	180
7067226FE8R	5000	4800	3.2	225	67	6.7	168
72161227FEHRSE	20000	19600	3.2	226.5	160.5	6.95	470
5596136FE	4200	4000	3.2V	5.7	96.5	137	127
75120130FE	7000	6500	3.2V	7.7	120.5	131	220
1178178FE	10000	9500	3.2V	11.2	78.5	179	260

7568270FE	10000	9500	3.2V	7.7	68.5	271	265
90100158FE	10000	9500	3.2V	9.2	100.5	159	260
85111233FE	15000	14500	3.2V	8.6	111.5	234	420
80180225FE	20000	19500	3.2V	8.2	180.5	226	555
90155225FE	20000	19500	3.2V	9.2	155.5	226	555
77205225FE	24000	23500	3.2V	7.9	205.5	226	670
80FE-H	80000		3.2V	46	167	264.5	2550
100FE-H	100000		3.2V	51	165	262.9	3580
120FE-H	120000		3.2V	66	167	264.5	4150
200FE-H	200000		3.2V	98	167	260	6450
220FE-H	220000		3.2V	106	165	262.9	7050
18650FE-HP	1000	950	3.2V	∅	18.6	65.6	37
18650FE-MP	1350	1250	3.2V	∅	18.6	65.6	37
26650HP-FE	2200	2100	3.2V	∅	26.1	65.9	78
26650MP2-FE	2800	2700	3.2V	∅	26.1	65.9	78
26700HE-FE	4000	3800	3.2V	∅	26.1	70	98
36800MP-FE	6000	5700	3.2V	∅	36.5	80.5	180